



Parquet system

The solution for parquet finish – completely available with us!

Hesse-Lignal is one of the leading specialists for wood lacquer in Europe and worldwide.

Our jobs are the development, production and sale of lacquers and stains for handicraft and industrial coating of wood; And this they are for almost 100 years now!

As supplier of the complete range of products for the surface treatment of wood in the interior sector, we have developed a parquet system, consisting of coating materials and stains in many attractive colours, which is perfectly adjusted to the demands of the parquet layers.

Hesse-Lignal is a one-stop supplier of all products for the finish of parquet. The application of these products by a skilled user guarantees a long-term protection of the valuable parquet floor. Surfaces, sealed with Hesse oils, PU- or Hydro lacquers are viscoplastic, hard-wearing, antisoiling and carefree.


So: The best materials for our times.

Parquet stains WPB 1....

Instead of classical parquet wood, we receive more and more inquiries for specially coloured parquet floorings. Besides the personal wishes of the customer, staining has also economic advantages. Low-price parquet wood can get a noble look, which is comparable to expensive exotic woods. 22 attractive, light fast colour tones are available, which are mixable with each other. Recoatable preferably with Hydro 1C- and 2C-finishes.

Please ask for our special parquet stain card: Order no.: **XPB**






Gap filling solution HS 10

- Flexible
- Free from solvents and plasticizers
- Good body
- Universally recoatable

Packaging size: 2,5 l

Efficiency: 50 m²/litre, depending on mixture and size of the gaps to be filled!





Hydro Base coat HG 20

- Fast drying
- Good levelling
- Good penetration into the substrate
- Minimizes the side/block-gluing

Packaging size: 5 l

Efficiency: 8-10 m²/litre





Hydro Putty gel HS 60

- For binding of rest dust after the first sanding of the Hydro-Sealer
- Closing of hairlines and wrinkles
- Thixotrope, fast drying, light fast
- Application between HE 30-degree of gloss and HDE 50-degree of gloss
- For normal and medium strain
- No substitute for HG 20 !

Packaging size: 5 l

Efficiency: 15-20 m²/litre



1C-Hydro Finish HE 30-


- Excellent abrasion resistance
- Very strong body
- Good resistance to foot marks
- Good light-fastness

Semi mat HE 30-4
Silky gloss HE 30-7

Packaging sizes: 1 / 5 l

Efficiency: 8-10 m²/litre each coat

Load range:



2C-Hydro Finish HDE 50-


- Excellent abrasion resistance
- Very strong body
- Very good light-fastness
- Excellent resistance to household chemicals

Mat HDE 50-2
Semi mat HDE 50-4
Silky gloss HDE 50-7
MR 10:1 with hardener HDR 70

Packaging size: 4,5 l

Efficiency: 8-10 m²/litre each coat

Load range:



1C-PU Finish DE 41-


- Extremely good abrasion resistance
- Very strong body
- To be applied without addition of hardener
- Resistance like a 2C-material

Mat DE 41-2
Semi mat DE 41-4
Silky gloss DE 41-6
Glossy DE 41-8

Packaging size: 5 l

Efficiency: 7-8 m²/litre each coat

Load range:



Oil Finish OE 80-


- Application by roll
- Good accentuation
- Good penetration on wooden floors, cork or OSB
- Forms a viscoplastic film
- For hardwearing surfaces
- After 10:1 mixture with OR 77, also applicable for highest strain
- Resistance depending on the application amount

Semi mat OE 80-4
glossy OE 80-7

Packaging sizes: 1 / 5 l

Efficiency: 25-33 m²/litre each coat

Load range:



Oil Finish OE 81-



- Hard-Oil finish for application by putty knife and rubbing in
- For medium strain
- On wooden floors, cork or OSB
- Good surface resistance
- Good resistance to foot marks
- Dirt-resistant
- After 10:1 mixture with OR 87, also applicable for highest strain
- Resistance depending on the application amount

Silky mat OE 81-2
Glossy OE 81-9

Packaging sizes: 1 / 5 l

Application by putty knife: 30-40 m²/litre each coat

Load range:



Maintenance oil OE 88-2

- Maintenance- and repair oil for oiled surfaces
- Rub in without surplus
- Varnishing of strained oiled floors
- Easy processing
- After 10:1 mixture with OR 87, also applicable for highest strain

Packaging size: 1 l

